

2-080.02 Swinghandle RS PrC

Key or tool actuation, IP65, Cutout B, Round rods, Soft design



Product Notes:

- Uses round rods
- Uses DIN 18252/18254 40mm profile cylinders, key cylinders or inserts
- Sliding dustcover is standard
- RH and LH application
- Uses 1, 2 or 3-point latching systems
- For IP65 applications the lower part of the swinghandle is sealed with a cap. For non IP65 applications the lower part has a fastening hook
- Dimensions of cutout PrC - see Product System 3-010
- Flat rod - see Product System 3-155.02

Material:

- **Swinghandle:** PA, Black
- **Dish:** PA, Black
- **Sliding cover:** PA, Black
- **Grounding clip:** Stainless Steel AISI 304



For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of symmetrical doors (as drawn) is:

$$L = \frac{\text{upper rod clearance} - 12\text{mm} (0.472)}{2 (0.079)} - 50\text{mm} (1.969) \quad L = \frac{\text{lower rod clearance} - 12\text{mm} (0.472)}{2 (0.079)} + 50\text{mm} (1.969)$$

For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of rod control at the door center is:

$$L = \frac{\text{clearance} - 12\text{mm} (0.472)}{2 (0.079)}$$

Swinghandle for profile cylinder 40mm long, up to 2.5mm protruding key-barrel part	Part No.	See Page
a) Installation with cap (IP65)	107-9005	
b) Dish with hook (IP65 not possible)	107-9007	
Swinghandle for profile cylinder 40mm long, with raised sliding cover for up to 5mm protruding key-barrel part		
a1) Installation with cap (IP65)	107-9006	
b1) Dish with hook (IP65 not possible)	107-9008	
c) Profile cylinder according DIN 18252		02.65
d) Swinghandle with fitted cylinder barrel		
Installation with cap (IP65)		
Keyed alike DIRAK 1333*	107-9018	
Keyed alike DIRAK DS200*	507-9210	
Keyed different	107-9020	
d1) as d), but dish with hook (no IP65 rating)		
Keyed alike DIRAK 1333*	107-9021	
Keyed alike DIRAK DS200*	507-9211	
Keyed different	107-9023	
Swinghandle for insert		
e) Installation with cap (IP65)	107-9024	
e1) Dish with hook (IP65 not possible)	107-9025	
f) Inserts must be ordered separately		02.63
Locking stub is included in handle-assembly.		
g) Assembling of inserts	207-0016	
Accessories d) to g).		02.44
Cams for 1-point latching		01.101
h) Grounding clip	208-1201.04	03.64
* with stainless dust-shutter		
i) Adapter for round rods		03.49, 03.50

2-080.02 Swinghandle RS PrC

Key or tool actuation, IP65, Cutout B, Round rods, Soft design

