

2-100.01 Swinghandle RS 105

Key or tool actuation, IP65, Cutout 105, Round rods



Product Notes:

- Uses round rods
- RH and LH application
- Insulated swinghandle
- Uses DIN 18252/18254 profile cylinders or a KABA Ø22 (0.866) round cylinder
- Water and dust tight according to IP65, DIN EN 60529
- Low profile design

Material:

- **Swinghandle:** PA, Black or Grey RAL 7032
- **3- and 2-point-cam** Steel, Zinc Plated
- **Round rods:** Steel, Zinc Plated
- **Adapter:** Zinc Die, Untreated
- **Rod Guide:** PA, Black



		Cutout 105/Ø46	See Page
a) Swinghandle, PA (Black) for profile cylinder 40mm long		207-9101	
a1) as a), but with dustcover		207-9102	
a2) as a1), but with profile cylinder 45mm long with cover		207-9103	
b) Swinghandle for Ø 22 KABA cylinder			
PA Black		207-9109	
PA Grey RAL 7032		207-7080*	
b1) as b), but with lead sealable dustcover			
PA Black		207-9110	
PA Grey RAL 7032		207-7043*	
b2) as b1), but with reinforced dustcover			
PA Black		207-9111	
PA Grey RAL 7032		207-7081*	
c) Swinghandle, PA (Black) with padlock device (AISI 304) for profile cylinder		207-9112	
Optional:			
d) 3-point-cam e.g. for bending	A20	207-9522	03.44
	A26	207-9528	
d1) 2-point-cam		207-9599	
e) Round rod			03.46, 03.47
f) Adapter for round rods			03.49, 03.50
g) Rod guide for bending	A20	200-3601.03	03.52, 03.53
Rod guide for bending	A26	200-3602.03	
h) Profile Cylinder according DIN 18252			02.65
i) KABA cylinder Ø 22 round cylinder on request			
k) Adapter ring to allow installation into 2 holes Ø46. In this case the same door can be used RH or LH.		207-2701.03	
k1) Gasket for adapter		207-2804	

* Quantity and delivery time on request.

2-100.01 Swinghandle RS 105

Key or tool actuation, IP65, Cutout 105, Round rods

