

## 2-100.02 Swinghandle RS 130

Key or tool actuation, IP65, Cutout 130, Round rods



### Product Notes:

- Uses round rods
- RH and LH application
- Insulated handle
- Uses DIN 18252/18254 profile cylinders or a KABA Ø22 (0.866) round cylinder
- Water and dust tight according to IP65, DIN EN 60529
- Low profile design

### Material:

- **Swinghandle:** Zinc Die, Black or PA, Black
- **3- and 2-point cam:** Steel, Zinc Plated
- **Round rods:** Steel, Zinc Plated
- **Adapter:** Zinc Die, Untreated
- **Rod Guide:** PA, Black



		Cutout 130/Ø46	Cutout 130/□46	See Page
a) Swinghandle, PA (Black) for profile cylinder 40mm long		207-9001	207-9311	
a1) as a), but with dustcover		207-9002	207-9312	
a2) Swinghandle, Zinc Die (Black) for profile cylinder 40mm long		207-9008	-	
a3) as a2), but with dustcover		207-9009	-	
a4) as a1), but 5mm raised for profile cylinder 45mm long with cover		207-9003	207-9313	
a5) as a4), but Swinghandle, Zinc Die (Black), door dish, PA Black for profile cylinder 45mm long		207-9004	207-9314	
<b>b) Swinghandle for Ø 22 KABA cylinder on request</b>				
c) Swinghandle, PA (Black) with padlock device (AISI 304) for profile cylinder		207-9006	on request	
<b>Optional:</b>				
d) 3-point-cam e.g. for bending	A20	207-9522	207-9522	03.44
	A26	207-9528	207-9528	
d1) 2-point-cam		207-9599	207-9599	
e) Round rods				03.46, 03.47
f) Adapter for round rods				03.49, 03.50
g) Rod guide for bending	A20	200-3601.03	200-3601.03	03.51, 03.52
Rod guide for bending	A26	200-3602.03	200-3602.03	
h) Profile cylinder according DIN 18252				02.65
<b>i) KABA cylinder Ø 22 round cylinder on request</b>				
k) Adapter ring to allow installation into 2 holes Ø46. In this case the same door can be used RH or LH.		207-2701.03	207-2701.03	
k1) Gasket for adapter		207-2804	207-2803	

# 2-100.02 Swinghandle RS 130

Key or tool actuation, IP65, Cutout 130, Round rods

