

3-155.02 Swinghandle FS PrC

Key or tool actuation, IP65, Cutout C, Flat rods, Soft design



Product Notes:

- Uses flat rods
- Use with rod latch systems
- Can be locked with 40mm long profile cylinders (DIN 18252/18254), key cylinder or insert
- For use with rod latch - see Product System 3-130, 3-132.01, 3-165 or 3-170.
- Dustcovers are standard
- For IP65 applications the lower part of the swinghandle is sealed with a cap. For non IP65 applications the lower part has a fastening hook
- Dimensions of cutout PrC - see Product System 3-010
- Round rod - see Product System 2-080.02

Material:

- **Swinghandle:** PA, Black
- **Dish:** PA, Black
- **Sliding cover:** PA, Black



Swinghandle for profile cylinder 40mm long, up to 2.5mm protruding key barrel part	Part No.	See Page
a) Installation with cap (IP65)	107-9001	
b) Dish with hook (IP65 not possible)	107-9003	
Swinghandle for profile cylinder 40mm long, with raised sliding cover for up to 5mm protruding key barrel part		
a1) Installation with cap (IP65)	107-9002	
b1) Dish with hook (IP65 not possible)	107-9004	
c) Profile cylinder according DIN 18252		02.65
d) Swinghandle with fitted cylinder barrel with cap and seals (IP65)		
Keyed alike DIRAK 1333*	107-9010	
Keyed alike DS200*	507-9208	
Keyed different	107-9012	
d1) as d) but dish with hook (no IP65 rating)		
Keyed alike DIRAK 1333*	107-9013	
Keyed alike DS200*	507-9209	
Keyed different	107-9015	
Swinghandle for insert		
e) Installation with cap (IP65)	107-9016	
e1) Dish with hook (IP65 not possible)	107-9017	
f) Inserts must be ordered separately. Locking stub included in handle assembly.		02.63
g) Assembling of inserts	207-0016	
Accessories		03.20, 03.57, 03.24, 03.64

* with stainless dustcover

3-155.02 Swinghandle FS PrC

Key or tool actuation, IP65, Cutout C, Flat rods, Soft design

