

7-065 Swinghandle RS PrC

Key or tool actuation, IP65, Stainless Steel, Cutout C, Round rods, Optional padlockable



Product Notes:

- Uses round rods
- Uses DIN 18252/18254 40mm profile cylinders with closing rotation or 45° or 90°
- RH and LH application
- Water and dust tight according to IP65, DIN EN 60529
- Dimensions of cutout PrC - see Product System 3-010
- A blanking (cover) plate is available to cover the opening for the padlock option in the swinghandle dish
- Opening rotation is 90°
- Other round rod - see Product System 2-090, 2-090SL and 2-091
- Tool-less installation - see Product System 2-090SL and 3-150SL
- Flat rod version - see Product System 3-150, 3-150SL, 3-151 and 7-060
- Other stainless steel - see Product System 7-060

Material:

- **Swinghandle, dish, dust cover, profile housing, snap cam, cam, adapter:** Stainless Steel AISI 316
- **Cap and rod guide:** PA, Black
- **Swinghandle shaft, padlock device, round rods:** Stainless Steel AISI 303
- **Insert, Cams and 3- and 2-point cam:** Stainless Steel AISI 303 or AISI 316
- **Grounding clip:** Stainless Steel AISI 301



For custom length rods as product system 7-106 the length L for rod control symmetrical doors (as drawn) is:

$$L = \frac{\text{upper rod clearance} - 12\text{mm}(0.472)}{2(0.079)} - 50\text{mm}(1.969) \quad L = \frac{\text{lower rod clearance} - 12\text{mm}(0.472)}{2(0.079)} + 50\text{mm}(1.969)$$

For custom length rods as product system 7-106 the length L for rod control at the door center is:

$$L = \frac{\text{clearance} - 12\text{mm}(0.472)}{2(0.079)}$$

Swinghandle for profile-cylinders to DIN 18252	Without Dustcover	With Dustcover	See Page
a) Swinghandle for profile-cylinder 40mm long	207-9294	207-9295	
a1) Blanking plate for opening (optional)	207-2506.80	207-2506.80	
a2) Swinghandle for padlock	107-9284	107-9285	
b) Profile-cylinder with insert			
Square 6mm	211-9226	211-9226	
Square 7mm	211-9227	211-9227	
Square 8mm	211-9228	211-9228	
Triangular 7mm	211-9229	211-9229	
Triangular 8mm	211-9230	211-9230	
Double bit 3mm pin	211-9231	211-9231	
Double bit 5mm pin	211-9232	211-9232	
Slotted 2x4mm deep	211-9233	211-9233	
Security insert with free rotating 8mm triangular front part.	211-9242*	211-9242*	02.65
Additional profile-cylinder			02.66, 02.65
c) 3-point cam for bending A20	207-9845-22	207-9845-22	
3-point cam for bending A26	207-9845-28	207-9845-28	
c1) 2-point cam	207-9598	207-9598	
Other dimensions of cams on request.			
d) Round Rod (see table above)			03.42, 03.48
e) Adapter for round rods			03.49, 03.50
f) Rod guide for bending A20	200-3601.03	200-3601.03	
Rod guide for bending A26	200-3602.03	200-3602.03	
g) Grounding clip	208-1201.04	208-1201.04	03.64
* Price and delivery time on request			

7-065 Swinghandle RS PrC

Key or tool actuation, IP65, Stainless Steel, Cutout C, Round rods, Optional padlockable

